

NILE Series


5.12/10.24KWH / Battery Group
Wall Mounted



MODEL	NILE-100		NILE-200	
Standard Voltage	51.2V			
Nominal Capacity	100AH		200AH	
Operating Voltage	42-58.4V			
Charging Current	50A		100A	
Max Charging/Discharging Current	100A			
Operating Temperature	0~40°C (Charging) , -20~40°C (Discharging)			
Storage Temperature	-10°C~35°C (1 Month) ,25±2°C (3 Month) ,65%±20%RH			
Cycle Life	6000 Cycles (25°C, 50A Charging/Discharging Current, 70%Standard Capacity, 80% DOD)			
Communication Interface	CAN&RS485			
Protection Class	IP20		Humidity Range	5-80%
Dimension(L*W*H)	395.5*563 162mm (Packaging Size 500*600*200mm)		638*860*180mm (Packaging Size 738*900*200mm)	
Weight	48±3kg (Gross Weight With Packaging 51kg)		103±3kg (Gross Weight With Packaging 103kg)	

SUNRISE ENERGY CO., LTD

Tel: +86-519-81688389 E-mail: info@sunriseenergy.cn
Add: No.20 Tongzi River West Road, Zhonglou Development Zone, Changzhou, Jiangsu, China

 If any update, Sunrise would not make further notice. Sunrise reserves the right of final interpretation.